



Dependable Gas Analysis Solutions

350 SERIES

PORTABLE FLUE GAS ANALYZER FOR OXYGEN & COMBUSTIBLES



APPLICATIONS

Analysis of oxygen (O_2) and combustibles. For checking the combustion efficiency, and burner & control performance of furnaces, heaters, and boilers. May be used in commercial, industrial, and residential settings.

FEATURES

- Rugged design, easy to operate, fast response
- Long-life electrochemical O_2 sensor
- Catalytic combustibles sensor
- Digital readout meter with backlight
- Rechargeable battery operation
- Built-in sample pump, filter and flowmeter
- Condensate removal bowl & pump
- Stainless steel probe with sample hose

OPTIONS

- 4-20mA recorder output
- Stack temperature readout (Model 350T)
- Sample pre-cooler
- Durable suitcase-style cabinet that is weather-proof when closed (K); display inside of cabinet
- Suitcase style cabinet with display moved to exterior (KX)
- Built-in data-logging to USB stick

CALIBRATION


- On air for O_2 span and combustibles zero.
- On analyzed mixture of carbon monoxide (CO), methane (CH_4), or hydrogen (H_2) in nitrogen for combustibles span and O_2 zero.



350K - standard suitcase enclosure (K)



350KX - suitcase enclosure
with external display (KX)



Optional
Ice Bath
Precooler

NOVA ANALYTICAL SYSTEMS

www.nova-gas.com

DESCRIPTION

The Nova 350 Series Portable Flue Gas Analyzer has been designed for accuracy, reliability, ease of use and ease of service. It uses customer replaceable sensors which respond quickly to the oxygen (O₂) and combustibles present in the flue gas sample. The sensor life expectancy is between 2 and 3 years.

In operation, a built-in sample pump draws in the flue gas sample through the stainless steel probe, 12 ft. (4 m) sample hose, condensate removal filter, secondary filter, flowmeter, then on to the oxygen and combustibles sensors. The detected O₂ and combustibles are displayed on LCD digital meter. A built-in air makeup system ensures that the combustibles detector will always have sufficient O₂ for proper operation regardless of sample O₂ content.

A rechargeable battery provides enough power for about 6 hours of continuous operation and the analyzer can be used while it is being recharged. The recharger is included.

SPECIFICATIONS

Nova reserves the right to specification changes which may occur with advances in design without prior notice.

Description

Method of Detection:	Customer replaceable electrochemical O ₂ sensor. Catalytic oxidation detector for combustibles. Expected life is 2-3 years for each. Stack temperature (Model 350T) using TypeK thermocouple in probe
Ranges Available:	0-25.0% O ₂ 0-5.0% or 0-10.0% combustibles 0-1800°F or 0-1000°C stack temperature (Model 350T) using TypeK thermocouple
Resolution:	0.1 %
Accuracy and Repeatability:	±1% full scale, based on 20.9% O ₂ ; ±2% of full scale combustibles
Drift:	<2% of full scale per 8 hours of continuous operation
Response Time:	5-8 seconds for O ₂ ; 20-30 seconds for combustibles
Ambient Temperature Range:	32° to 105°F (0° - 40.5°C)
Linearity:	±1% full scale, based on 20.9% O ₂ ; ±2% of full scale combustibles
Size and Weight:	Approx. 35.5L x 15.2H x 26.6D cm @ 5.5 kg (14" x 6" x 10½" @ 8 lbs)
Power:	AC/DC operation, 115VAC 60Hz for recharging (other voltages available)
Output Options:	4-20mA

UNIQUE APPLICATIONS

The 350 Series should not be used for detecting these gases in ambient atmospheres for personnel safety purposes. All Nova analyzers are built using proven technologies and techniques. If this product does not suit your application, please contact Nova at 1-800-295-3771. In many cases, we are able to build an analyzer specific to your needs.



NOVA ANALYTICAL SYSTEMS
(A UNIT OF TENOVA GOODFELLOW INC.)

IN USA:
4450 Witmer Industrial Estates, Unit 4 • Niagara Falls, NY • 14301
Tel: 1-800-295-3771 • 716.285.0418 • Fax: 716.282.2937
IN CANADA:
270 Sherman Avenue North • Hamilton, ON • L8L 6N5
Tel: 905.545.2003 • Fax: 905.545.4248
emails:
sales@nova-gas.com / websales@nova-gas.com



www.nova-gas.com