

NOVA

Dependable Gas Analysis Solutions



436 SERIES

TRI-GAS ANALYZER FOR MONITORING PURITY AND PURGING OF HYDROGEN COOLED POWER GENERATORS

APPLICATIONS

For continuous analysis of hydrogen (H₂) purity and for purge monitoring of hydrogen-cooled generators and synchronous converters.

FEATURES

- One analyzer monitors all 3 gases for purity (Range 1) or purging (Ranges 2 and 3):
 - **Range 1:** 0-100% H₂ in Air
 - **Range 2:** 0-100% H₂ in CO₂
 - **Range 3:** 0-100% Air in CO₂
- Bright digital readout
- 4-20 mA isolated output for 85-100% of H₂ in Air
- Thermal-conductivity cell with high accuracy and repeatability, cannot be burned out.
- Explosion-proof gas detector enclosure suitable for Class 1 Division 1 Group BCD rated areas
- Fast response (T₉₀ -10 to 15 secs)
- Built in pressure regulator

OPTIONS

- Isolated 4-20mA output for any range selected
- 2 levels of low H₂ purity alarms & detector fail alarm
- Automatic Calibration by microprocessor control available on N7MC configuration
- Serial output with data-logging software
- Oil vapor filter assembly

CALIBRATION

- Channel 1 - Air for Zero, 100% H₂ for Span
- Channel 2 - 100% CO₂ for Zero, 100% H₂ for Span
- Channel 3 - 100% CO₂ for Zero, Air for Span

NOVA ANALYTICAL SYSTEMS

www.nova-gas.com



NEMA 7 Gas Detector Cabinet

Choice of Control Cabinet as follows:



NEMA 4 Control Cabinet

or:



19" Rack Mount Control Cabinet



Also available:

Standalone NEMA 7 Control and Detector Cabinet



Important accessory:

Oil Vapor Filter Assembly
- protects analyzer from sensor fouling caused by oil-vapors from power generator

DESCRIPTION

The Nova Model 436RMN7 Tri-gas analyzer is designed specifically for monitoring H₂ purity in a power generator and to monitor the purging procedure during shut down. The analyzer can measure the following gases by switch selection: **Range 1:** 0-100.0% H₂ in Air; **Range 2:** 0-100.0% H₂ in CO₂; **Range 3:** 0-100.0% Air in CO₂. An isolated 4-20 mA recorder output is provided for the range of 85-100% H₂ in Air.

The Model 436 analyzer is typically divided into 2 sections which are electrically connected. The control section contains the main microprocessor board as well as the digital readout meters, alarms, calibration and range switches, power supply and temperature controller for the T/C cell. The gas detector section contains the temperature controlled thermal-conductivity (TC) cell, a five way selector valve, gas pressure regulator, flow indicator and 2 flame arrestors.

Either the gas detector section on its own or both gas detector and control sections may be purchased in explosion-proof cabinets. The explosion-proof cabinets are UL listed and CSA certified for use in Class 1, Division 1, Groups BCD hazardous areas. If the gas detector section only is explosion-proof, the control section is typically enclosed in a 19" rack mount cabinet for use in a general purpose, non-hazardous area. The control section can also be mounted in a NEMA 4 wall mount cabinet.

MODELS

- **436N4N7** - gas detector in explosion-proof cabinet; control section in general purpose NEMA 4 cabinet
- **436RMN7** - gas detector in explosion-proof cabinet; control section in general purpose 19" rack mount cabinet
- **436N7MC** - gas detector and controls located in single explosion-proof cabinet

SPECIFICATIONS

Nova reserves the right to specification changes which may occur with advances in design without prior notice.

Description	
Method of Detection:	Temperature controlled thermal conductivity (T/C) cell, cannot be burned out due to loss of flow or changing gases
Ranges Available:	Range 1: 0-100% H ₂ in Air; Range 2: 0-100% H ₂ in CO ₂ ; Range 3: 0-100% Air in CO ₂
Resolution:	± 0.1% of gas measured
Accuracy and Repeatability:	± 1% F.S except in 85-100% H ₂ in Air output range which is within 0.2% absolute H ₂
Drift:	H ₂ in CO ₂ or Air in CO ₂ , 1% F.S. per week maximum drift, 0-100% H ₂ in Air range is ± 0.2% per week
Response Time (T-90):	10-15 seconds to 90% step change - not including sample transport time
Ambient Temperature Range:	32-120°F (0-50°C)
Linearity:	± 0.4% of F.S. on H ₂ in Air range, ± 1% of F.S. in H ₂ or Air in CO ₂ ranges
Size and Weight:	Dimensions will vary depending on enclosure style and options required
Power:	115VAC 60Hz (220VAC 50Hz available)
Output Options:	4-20 mA into 500 ohms isolated - standard for 85-100% H ₂ in Air range Optional - Isolated 4-20mA for any range selected, serial RS485 / RS232 / USB
Alarms:	Optional dual alarms for low H ₂ purity and detector fail. Alarms have front panel light for each alarm and SPDT (normally energized) relay with 5A rating at 250VAC non-inductive load. Alarm set points are field adjustable.



NOVA ANALYTICAL SYSTEMS
A UNIT OF TENOVA GOODFELLOW INC.

IN USA:
1925 Pine Avenue • Niagara Falls, NY • 14301
Tel: 1-800-295-3771 • 716.285.0418 • Fax: 716.282.2937
IN CANADA:
270 Sherman Avenue North • Hamilton, ON • L8L 6N5
Tel: 905.545.2003 • Fax: 905.545.4248
email: sales@nova-gas.com
websales@nova-gas.com



www.nova-gas.com